



INDUSTRIAL PUMPING PTY LTD

FLUID MANAGEMENT SPECIALISTS

76 Scott Street, Cairns. Australia. sales@pumping.com.au Ph: 617-40312755 Fax: 617-40314416

Grundfos-Mono-Calpeda-Ebara-Flygt-Lowara-ABS-Stalker-Wilden-SIHI-Zenit-Amiad-Bredel-Bermad-Dorot-Kelco-AUV

LCP uPVC Series Ultra Violet Technical Data & Prices

Designed specifically for Aquaculture and other salt-water applications, using a uPVC corrosion resistant reactor. The uPVC units should only be used where there is a constant water flow.

UV Reactor

- Max. Operating Pressure 550 kPa.
- Vessel: Z shaped, 100% uPVC wetted surface.
- 2" solvent weld joint uPVC Inlet & Outlet.
- Horizontal Mounting Preferred.

UV Lamps

- Cylindrical Low Pressure High Intensity UV Lamp
- UV Lamp sleeve: Fused quartz, open one end. Designed for easy removal

Electrical Control Cabinet

- Single Phase 240V, 50Hz supply with 1.5 metres of Lamp Connect Cable
- IP23 Fan Cooled with lamp fail alarm

Model LCP-4 & 8

Model LCP-4 LCP-8

UV Reactor:

Inlet / Outlet	2" uPVC	2" uPVC
Dimensions	900x110	900x110
Flow clear water (l/hr)	4,000	8,000
Dry weight (kg)	7	7

UV Lamps/thimbles:

Lamp part No.	GXO-860L	W-37087
Lamp Power (W)	40	80
Lamp Life Hours	9000	12,000
Quartz Thimble part No.	VSL900	VSL900
Thimble O-Ring part No.	W-35492	W-35492

Electrical Cabinet:

Size mm (approx)	290x130x80	370x270x165
Weight kg (approx)	2.0	2.5
Power Consumption (W)	44	88
Enclosure Type (std)	Fan Cooled	Fan Cooled

Export Prices:

\$1,125.00 \$2,080.00

Prices are ex our store. They include power box, cables, UV reactor, fragile packing and are exclusive of GST.

Spare Parts:

O ring seal for thimble	\$12.00	\$12.00
UV lamp	\$170.00	\$225.00
Quartz Thimble QT	\$170.00	\$170.00

Special fragile packing charge (per spare parts consignment), \$10.00

